



VIMASCO CORPORATION

P.O. Box 516 * Nitro, WV 25143 * (304) 755-3328
 Toll Free (800) 624-8288 * Fax (304) 755-7153
 www.vimasco.com

MATERIAL SAFETY DATA SHEET — 16 Sections

SECTION 1 — CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

| | | | |
|---|---------------------------------------|------------------------------------|---------------------|
| Product Identifier WC-7 Type C | | July 11, 2017 | |
| Product Use Cork-Filled Vinyl Acrylic Mastic Weather Barrier | | | |
| Manufacturer's Name Vimasco Corporation | | Supplier's Name | |
| Street Address 280 W. 19th St., Republic Way | | Street Address | |
| City Nitro | State: WV | City | |
| Postal Code 25143 | Emergency Phone (304) 206-7803 | Postal Code | Emergency Telephone |
| Prepared by: John Tidquist | | Phone Number (304) 755-3328 | |

SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

| Hazardous Ingredients (<i>specific</i>) | % | CAS Number | LD ₅₀ of Ingredient (<i>specify species and route</i>) | LC ₅₀ of Ingredient (<i>specify species</i>) |
|---|-------|------------|---|---|
| Dipropylene Glycol Dibenzoate | 3 – 4 | 20109-39-1 | Not established | 2.29 x 10 ⁻⁷ mmHg 77°F |
| | | | | |
| | | | | |
| | | | | |

SECTION 3 — HAZARDS IDENTIFICATION

| |
|---|
| <p>Primary Routes of Entry: Dermal or inhalation</p> <p>Dipropylene Glycol Dibenzoate: Mild irritation to eyes, skin and nasal passages.</p> <p>LD₅₀(oral) 2,500 mg/kg RAT LD₅₀ (dermal) 2,500 mg/kg Rabbit LD₅₀ (inhalation) 200 mg/l (4 hr.) RAT</p> <p>Medical Conditions Prone to Aggravation by Exposure: None known</p> |
|---|

Product Identifier - WC-7 Type C, Vimasco Corporation

SECTION 4 — FIRST AID MEASURES

Skin: Wash with soap and water

Eyes: Flush with clean water at least 15 minutes, if irritation persists, consult physician.

Inhalation: Remove to fresh air. If breathing is difficult, administer oxygen. If irritation persists, consult physician

Ingestion: Give two glasses of water, induce vomiting, consult physician or poison control center. Never give anything by mouth to an unconscious person.

SECTION 5 — FIRE FIGHTING MEASURES

| | | |
|---|-------------------------------------|--|
| Flammable No | If yes, under which conditions? | |
| Means of Extinction: Foam, Alcohol Foam, CO ₂ , Dry Chemical, Water Fog | | |
| Flashpoint: No flash to boiling 212°F (TCC) | Upper Flammable Limit (% by volume) | Lower Flammable Limit (% by volume) |
| Autoignition Temperature (°C) | Explosion Data: None known | Explosion Data — Sensitivity to Static Discharge |
| Hazardous Combustion Products : None known | | |
| Product will not burn until water has boiled or evaporated. For dried film or residual solids, full protective equipment is recommended, including self-contained breathing apparatus | | |

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Spills should be collected for disposal; eliminate all ignition sources. Prevent material from entering drains, sewers and waterways. Spills may be slippery. Before drying product may be washed away with water; after drying, remove with a paint scraper or strong solvent.

SECTION 7 — HANDLING AND STORAGE

Thoroughly cleanse hands after handling. Launder contaminated clothing before reuse.

Protect from freezing.

Do not use empty containers for potables or edibles.

Store indoors at temperatures of 40°F to 90°F. Do not store at elevated temperatures, as containers could pressurize and rupture

Product Identifier: WC-7 Type C, Vimasco Corporation

SECTION 8 — EXPOSURE CONTROL / PERSONAL PROTECTION

Exposure limits: Not available

In restricted ventilation areas, use approved chemical respirator, avoid inhalation of airborne particulates by using an approved respirator. General (mechanical) room ventilation is expected to be satisfactory. Supplementary local exhaust and respiratory protection may be needed in poorly ventilated spaces, or evaporation from large surfaces when spraying.

Personal Protection: Impervious gloves, goggles, face shield or other eyewear to protect from splash. Thoroughly cleanses hands after handling. Launder contaminated clothing before reuse.

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|-------------------------------------|---|--|
| Physical State: Paste consistency | Odor: Mild latex odor | Wt/Gal: 7.8 lbs. |
| Specific Gravity: 1.26 | Vapor Density (air = 1): Lighter than air | Viscosity: Approx. 80,000 cps (spray grade); |
| Evaporation Rate: Slower than ether | Boiling Point: 212°F | Freezing Point: 32°F (0°C) |
| pH 8.0 to 9.0 | VOC (lbs/gal): 37 gm/L; (0.31 lbs/gal) | Volatile Volume: 50% (water) |

SECTION 10 — STABILITY AND REACTIVITY

Chemical Stability: Stable

Avoid materials that are incompatible with water.

Thermal decomposition will yield CO, CO₂.

Decomposition Temperature: Approximately 240°F (115°C)

SECTION 11 — TOXICOLOGICAL INFORMATION

Not available

SECTION 12 — ECOLOGICAL INFORMATION

Not available

Product Identifier: WC-7 Type C, Vimasco Corporation

SECTION 13 — DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable regulations. Review hazard section of this sheet before attempting cleanup. Major spills should be collected for disposal. Minor spills may be flushed to sewer if regulations permit. Before drying product may be washed away with water; after drying, remove with a paint scraper, or strong solvent.

Empty containers are non hazardous under RCRA as industrial waste.

SECTION 14 — TRANSPORT INFORMATION

Not regulated.

SECTION 15 — REGULATORY INFORMATION

None

SECTION 16 — OTHER INFORMATION

For industry/professional use only. Not intended for retail sale or use by individual consumers.

HMIS Hazard Rating

Health: 1 Flammability: 0 Physical Hazard: 0

NFPA

Health: 1 Flammability: 0 Reactivity: 0