



# VIMASCO CORPORATION

P.O. Box 516 \* Nitro, WV 25143 \* (304) 755-3328  
 Toll Free (800) 624-8288 \* Fax (304) 755-7153  
 www.vimasco.com

## MATERIAL SAFETY DATA SHEET — 16 Sections

### SECTION 1 — CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier LC-5 Log Chinking		February 20, 2019	
Product Use Latex based Coating (Mixture)			
Manufacturer's Name Vimasco Corporation		Supplier's Name	
Street Address 280 W. 19 <sup>th</sup> St., Republic Way		Street Address	
City Nitro	State: WV	City	
Postal Code 25143	Emergency Phone (304) 206-7803	Postal Code	Emergency Telephone
Prepared by: John Tidquist		Phone Number (304) 755-3328	

### SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients ( <i>specific</i> )	%	CAS Number	LD <sub>50</sub> of Ingredient ( <i>specify species and route</i> )	LC <sub>50</sub> of Ingredi
Vinyl Acetate (residual monomer)	<0.2	108-05-4	10ppm (TWA ACGIH)	Not established
Acrylate (residual monomer)				

### SECTION 3 — HAZARDS IDENTIFICATION

Vinyl Acetate & Acrylate: Contains some residual monomers which are toxic if inhaled in high concentrations and may cause respiratory and skin irritations. Vinyl acetate has been shown to cause cancer in laboratory animals.

Medical Conditions Prone to Aggravation by Exposure: None known

Primary Routes of Entry: Dermal or Inhalation

## Product Identifier - LC-5, Vimasco Corporation

### SECTION 4 — FIRST AID MEASURES

**Skin:** Wash with soap and water

**Eyes:** Flush with clean water at least 15 minutes, if irritation persists, consult physician.

**Inhalation:** Remove to fresh air. If breathing is difficult, administer oxygen. If irritation persists, consult physician

**Ingestion:** Give two glasses of water, induce vomiting, consult physician or poison control center. Never give anything by mouth to an unconscious person.

### SECTION 5 — FIRE FIGHTING MEASURES

Flammable No	If yes, under which conditions?	
Means of Extinction: Foam, Alcohol Foam, CO <sub>2</sub> , Dry Chemical, Water Fog		
Flashpoint: No flash to boiling 212°F (TCC)	Upper Flammable Limit (% by volume)	Lower Flammable Limit (% by volume)
Autoignition Temperature (°C)	Explosion Data: None known	Explosion Data — Sensitivity to Static Discharge
Hazardous Combustion Products : Thermal decomposition will yield CO, and CO <sub>2</sub>		
Product will not burn until water has boiled or evaporated. For dried film or residual solids, full protective equipment is recommended, including self-contained breathing apparatus		

### SECTION 6 — ACCIDENTAL RELEASE MEASURES

Spills should be collected for disposal; eliminate all ignition sources. Prevent material from entering drains, sewers and waterways. Spills may be slippery. Before drying product may be washed away with water; after drying, remove with a paint scraper or strong solvent.

### SECTION 7 — HANDLING AND STORAGE

Thoroughly cleanse hands after handling. Launder contaminated clothing before reuse.

Protect from freezing.

Do not use empty containers for potables or edibles.

Store indoors at temperatures of 40°F to 90°F. Do not store at elevated temperatures, as containers could pressurize and rupture

**Product Identifier: LC-5, Vimasco Corporation**

**SECTION 8 — EXPOSURE CONTROL / PERSONAL PROTECTION**

Exposure limits: Not available

In restricted ventilation areas, use approved chemical respirator, avoid inhalation of airborne particulates by using an approved respirator. General (mechanical) room ventilation is expected to be satisfactory. Supplementary local exhaust and respiratory protection may be needed in poorly ventilated spaces, or evaporation from large surfaces when spraying.

Personal Protection: Impervious gloves, goggles, face shield or other eyewear to protect from splash. Thoroughly cleanses hands after handling. Launder contaminated clothing before reuse.

**SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES**

Physical State: Paste consistency	Odor: Mild latex odor	Wt/Gal: 12 lbs.
Specific Gravity: 1.44	Vapor Density (air = 1): Lighter than air	Viscosity: Approx. 2 million cps (Brookfield)
Evaporation Rate: Slower than ether	Boiling Point: 212°F to 216°F	Freezing Point: 32°F (0°C)
pH 8.0	VOC (lbs/gal): 14 gm/L (.117 lb/gl)	Volatile Volume: 30% (water)

**SECTION 10 — STABILITY AND REACTIVITY**

Chemical Stability: Stable

Avoid materials that are incompatible with water.

Thermal decomposition will yield CO, CO<sub>2</sub>, HPO<sub>x</sub>

**SECTION 11 — TOXICOLOGICAL INFORMATION**

Not available

**SECTION 12 — ECOLOGICAL INFORMATION**

Not available

**Product Identifier: LC-5, Vimasco Corporation**

**SECTION 13 — DISPOSAL CONSIDERATIONS**

Dispose of in accordance with all applicable regulations. Review hazard section of this sheet before attempting cleanup. Major spills should be collected for disposal. Minor spills may be flushed to sewer if regulations permit. Before drying product may be washed away with water; after drying, remove with a paint scraper, or strong solvent.

Empty containers are non hazardous under RCRA as industrial waste.

**SECTION 14 — TRANSPORT INFORMATION**

Not regulated.

**SECTION 15 — REGULATORY INFORMATION**

**None**

**SECTION 16 — OTHER INFORMATION**

For industry/professional use only. Not intended for retail sale or use by individual consumers.

**HMIS Hazard Rating**

Health: 1      Flammability: 0      Physical Hazard: 0

**NFPA**

Health: 1      Flammability: 0      Reactivity: 0