



# VIMASCO CORPORATION

P.O. Box 516 \* Nitro, WV 25143 \* (304) 755-3328  
Toll Free (800) 624-8288 \* Fax (304) 755-7153  
www.vimasco.com

## S D S

### SAFETY DATA SHEET — 16 Sections

#### SECTION 1 — CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier <b>739 Ultra Finish BrushSeal™ Coating</b>		January 3, 2022	
Product Use <b>Water-based Vapor Barrier Coating</b>			
Manufacturer's Name <b>Vimasco Corporation</b>		Supplier's Name	
Street Address <b>280 W. 19<sup>th</sup> St., Republic Way</b>		Street Address	
City <b>Nitro</b>	State: <b>WV</b>	City	
Postal Code <b>25143</b>	Emergency Phone <b>(304) 206-7803</b>	Postal Code	Emergency Telephone
Prepared by: <b>John Tidquist</b>		Phone Number <b>(304) 755-3328</b>	

#### SECTION 3 — HAZARDS IDENTIFICATION

<p><b>Primary Routes of Entry:</b> Dermal or inhalation  <b>Eye:</b> May be an irritant; <b>Skin:</b> Prolonged contact may cause irritation dermatitis;  <b>Ingestion:</b> No information assumed to cause gastro irritation. Low toxicity;  <b>Inhalation:</b> May cause irritation to the respiratory tracts. Overexposure could cause headache, nausea, fatigue.  <b>GHS Labeling:</b> Not a hazardous mixture </p>
---

#### SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients ( <i>specific</i> )	%	CAS Number	LD <sub>50</sub> of Ingredient ( <i>specify species and route</i> )	LC <sub>50</sub> of Ingredi
Aqua Ammonia	0.06 – 0.09	1336-21-6	Oral rat 350 mg/kg	Inhalation rat 5000 ppm

#### SECTION 4 — FIRST AID MEASURES

<p><b>Skin:</b> Wash with soap and water  <b>Eyes:</b> Flush with clean water at least 15 minutes, if irritation persists, consult physician.  <b>Inhalation:</b> Remove to fresh air. If breathing is difficult, administer oxygen. If irritation persists, consult physician  <b>Ingestion:</b> Give two glasses of water, induce vomiting, consult physician or poison control center. Never give anything by mouth to an unconscious person.</p>
--

**Product Identifier: 739 Ultra Finish BrushSeal, Vimasco Corporation**

**SECTION 5 — FIRE FIGHTING MEASURES**

Flammable No	If yes, under which conditions?	
Means of Extinction: Alcohol Foam CO <sub>2</sub> , Dry Chemical, Water Fog		
Flashpoint: No flash to boiling 212°F (TCC)	Upper Flammable Limit (% by volume) No data available	Lower Flammable Limit (% by volume) No data available
Autoignition Temperature (°C) No data available	Explosion Data: None known	Explosion Data — Sensitivity to Static Discharge None
<b>Hazardous Combustion Products</b> :Thermal decomposition will yield CO, CO <sub>2</sub> , HPO <sub>x</sub> , and fragmented short-chain hydrocarbons		
Product will not burn until water has boiled or evaporated. For dried film or residual solids, full protective equipment is recommended, including self-contained breathing apparatus		

**SECTION 6 — ACCIDENTAL RELEASE MEASURES**

Spills should be collected for disposal. Prevent material from entering drains, sewers and waterways. Spills may be slippery. Before drying product may be washed away with water; after drying, remove with a paint scraper or strong solvent.

**SECTION 7 — HANDLING AND STORAGE**

Thoroughly cleanse hands after handling. Launder contaminated clothing before reuse.  
Protect from freezing.  
Do not use empty containers for potables or edibles.  
Store indoors at temperatures of 40°F to 90°F. Do not store at elevated temperatures, as containers could pressurize and rupture  
Spills may be slippery.

**SECTION 8 — EXPOSURE CONTROL / PERSONAL PROTECTION**

Exposure limits: Not available

In restricted ventilation areas, use approved chemical respirator, avoid inhalation of airborne particulates by using an approved respirator. General (mechanical) room ventilation is expected to be satisfactory. Supplementary local exhaust and respiratory protection may be needed in poorly ventilated spaces, or evaporation from large surfaces when spraying.

Personal Protection: Impervious gloves, goggles, face shield or other eyewear to protect from splash.

**SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES**

Physical State: Paste consistency	Odor : Mild latex odor	Wt/Gal: 10.5 lbs.
Specific Gravity: 1.26	Vapor Density (air = 1): Lighter than air	Viscosity: Approx. 160,000 – 170,000 cps
Evaporation Rate: Slower than ether	Boiling Point : 212°F to 216°F	Freezing Point : 32°F (0°C)
pH 8.0 to 9.0	VOC (lbs/gal): 0 gm/L; 0.0 lbs/gal (less water)	Volatile Volume: 50%

**SECTION 10 — STABILITY AND REACTIVITY**

Chemical Stability: Stable

Avoid materials that are incompatible with water and oxidizers.

Decomposition Temperature: Approximately 240°F (115°C).

**SECTION 11 — TOXICOLOGICAL INFORMATION**

Not available

**SECTION 12 — ECOLOGICAL INFORMATION**

Not available

**SECTION 13 — DISPOSAL CONSIDERATIONS**

Dispose of in accordance with all applicable regulations. Review hazard section of this sheet before attempting cleanup. Spills may be slippery. Before drying, product may be washed away with water; after drying remove with a paint scraper or strong solvent. Empty containers are non hazardous under RCRA as industrial waste.

**SECTION 14 — TRANSPORT INFORMATION**

U.S. Dept. of Transportation (DOT): Not regulated

International Maritime Dangerous Goods Code (IMDG): Not regulated

**SECTION 15 — REGULATORY INFORMATION**

SARA Title III, Section 302, 311/312, 313: None

CERCLA – Reportable Quantity: None

**SECTION 16 — OTHER INFORMATION**

For industry/professional use only. Not intended for retail sale or use by individual consumers.

HMIS Hazard Rating

Health: 1      Flammability: 0      Physical Hazard: 0

NFPA

Health: 1      Flammability: 0      Reactivity: 0